



SAFETY JOGGER

INDUSTRIAL



Medium

ALASKA C PRO S3

ALASKACPRO

##

Safety Jogger ALASKA C PRO# ##### ## ## ## ## ##. ###
###, ### ##, ### #####. ##### ## ## ## ##.

## ##	## ##### ##
## ##	####
###	SJ # ##
##	##
###	##
Top	##
####	S3 / SR, FO, HRO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.830 kg
###	ASTM F2413:2018 EN ISO 20345:2022




DBN



#####. 100##### 1### ##
##



300°C# ## ## # ##.




##.



##.



##(SR)
SRA+SRB=SRC ##
#####. SR# ## ## ## ## ##
##.



##, ## # ##, ##
##, ##, ## # ## ##

##.

SAFETY JOGGER

WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
##, ###, ## # ##, ##

##:
##, ### ##, ### ##, ## ##, ### ## ##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##### ##			
	##: ### ##	mg/cm²/h	2.0	≥ 0.8
	##: ### ##	mg/cm²	17	≥ 15
## ##	####			
	##: ### ##	mg/cm²/h	28.68	≥ 2
	##: ### ##	mg/cm²	230	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	##			
	### #####(## ##)	mm³	Relative volume loss:123g/cm³(Density:1.14)	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.42	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.45	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.33	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.33	≥ 0.22
	### ## #	###	20.9	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	53	≥ 20
	##			
Top	#### ## #(## # ##### 100J)	mm	NA	N/A
	#### ## #(## # ## ## 10kN)	mm	NA	N/A
	#### ## #(## # ## ## 200J)	mm	19.0	≥ 14
	#### ## #(## # ## ## 15kN)	mm	22.5	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ## ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com