



#

ALTO TLS

ALTOTLS

ALTO ##### ## ##, ##, ## ## # #### ## ## ##
#####. ESD, ### ##, ## ##, ##### ## ## ## ## ##. ALTO#
TLS ##### #####.

## ##	##, ##
## ##	##
###	SJ ### # ###
##	N/A
###	###/##
Top	####
####	SR, ESD, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.426 kg



DBL



BLK



TLS(#### ## ##)

Safety Jogger # #### TLS ##
#####. ##
##, ## #####
#####. ### ##### TLS #####
#####. ##
#####.




####

#####.



####

#####.



####

##.



####

ESD# ## ## ## ## # ## ##

100####
100#### #####.



####

#####.

##:
####, ###, ##, ##, ## # ##

##:
##, ## ##### ##, ###

##:
#####. ### ##### ## ##### ### ##.

	##	## ##	##	
## ##	##, ##			
	##: ### ##	mg/cm²/h	4.87	≥ 0.8
	##: ### ##	mg/cm²	40	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	2.99	≥ 2
	##: ### ##	mg/cm²	31	≥ 20
###	SJ ### # ###			
	###: #####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	###/##			
	### #####(## ##)	mm³	128(Density:1.17)	≤ 150
	## ### ## - ### + NaLS - ## ### #####	##	0.43	≥ 0.31
	## ### ## - ### + NaLS - ## ## ###	##	0.44	≥ 0.36
	SR ### ## - ### + ##### - ##### ### ##	##	0.37	≥ 0.19
	SR ### ## - ### + ##### - ## ## ###	##	0.35	≥ 0.22
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	24	0.1 - 100
	#### ### ##	J	N/A	≥ 20
Top	####			
	#### ## # (## # ##### 100J)	mm	20.5	N/A
	#### ## # (## # ## ## 10kN)	mm	23.5	N/A
	#### ## # (## # ## ## 200J)	mm	N/A	N/A
	#### ## # (## # ## ## 15kN)	mm	N/A	N/A

##:

###, ## ## ##### ### # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ### ## ##### ##### ### # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com