



Medium

ASAMA S3S MID TLS

ASAMAS3MTL

TLS, ### ##### #, Phylon ## ### ## ### #####.

Safety Jogger ASAMAS3MTL# ##### ## ## ## ## ## ## ## ## ##.

TLS ###, ## ## ## ##, ### ## # ESD# #####.

## ##	##, ##
## ##	##
###	SJ ### # ###
##	## ## ##
###	###/##
Top	##
####	S3S / SR, ESD, ##, CI, FO, HRO
## ##	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0
	JPN 21.5-31 / KOR 230-310
###	ASTM F2413:2018
	EN ISO 20345:2022+A1:2024




TLS(#### ## ###)

Safety Jogger # ##### TLS ##

##, ## ## ## ##
#####. ### ## ## TLS #####

##.



##


#####. ## ## ##### ## ##
#####.



##

ESD# ## ##### # ## ##


#####. ## ## ## 100#####
100### #####.



##

##, ## # ##, ##
##, ##, ## # ## ##

#####.



####

##.



##(SR)

SRA+SRB=SRC ##
#####. SR# ## ## ## ## ##
##.

##:
####, ###, ##, ##, ###

##:
##, ## ##### ##, ##

##:
#####. ### ##### ## ##### ### ##.

	##	## ##	##	EN ISO 20345
## ##	##, ##			
	##: ### ##	mg/cm²/h	21.09	≥ 0.8
	##: ### ##	mg/cm²	169	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	49.8	≥ 2
	##: ### ##	mg/cm²	398.8	≥ 20
###	SJ ### # ###			
	###: #####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	###/##			
	### #####(## ##)	mm³	128	≤ 150
	## ### ## - ### + NaLS - ## ### #####	##	0.48	≥ 0.31
	## ### ## - ### + NaLS - ## ## ###	##	0.43	≥ 0.36
	SR ### ## - ### + ##### - ##### ### ##	##	0.41	≥ 0.19
	SR ### ## - ### + ##### - ## ## ###	##	0.34	≥ 0.22
	### ## #	###	14.6	0.1 - 1000
	ESD #	###	11.6	0.1 - 100
	#### ### ##	J	35	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	18.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	23.0	≥ 14

##:
###, ## ## ##### ### # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ### ## ##### ##### ### # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com