



#

ATUM OB

ATUMOB

##

ATUM OB(Safety Jogger)# #### ## ## ## ## ## ## ## ##
#####. ##, ##, ## # #### #####.

## ##	## ##
## ##	##
###	SJ # ##
###	TPR/EVA
####	OB / SR, E
## ##	EU 35-48
## ##	0.338 kg
###	EN ISO 20347:2022+A1:2024



BLK




LGR



#####.



##(SR)
SRA+SRB=SRC ###
#####. SR# ### ##### ## ##
#####.



#####.



SJ FOAM

#, ## # ## ##
#####. ## # ## ##.

##:
####, ####, ##, ##

##:
##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20347
## ##	## ##			
	##: ### ##	mg/cm²/h	63.6	≥ 0.8
	##: ### ##	mg/cm²	509.2	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	11.7	≥ 2
	##: ### ##	mg/cm²	94.2	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	TPR/EVA			
	### #####(## ##)	mm³	104.4	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.39	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.40	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.20	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.23	≥ 0.22
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	43	≥ 20

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.