

Heavy

BASALT S7S

###

BASALT ## ##### ## ## #####. ##### ## ## ## ## ##
SR ### ##, ###, ### ##, ## ##, ## ## ##, ### ## # ### ## ##
#####. ### ## ## #####.

## ##	#### ## ##, ##
## ##	####
###	SJ # ##
##	## ## ##
###	PU/##
Top	##
####	S7S / SR, SC, LG, ESD, ##, CI, FO, HRO
## ##	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
## ##	0.820 kg
###	ASTM F2413:2018 EN ISO 20345:2022




S3
S3 ##### ## ## ## ## ##

#####.



###
ESD# ## ## ## ## ## ##

#####. ## ## ## 100#####
100### #####.



###

#####. ## ## ## ## ## ##
#####. ## ## ## ## ## ##.




##

#####.



SRC

#####. SRC ### ## ##
SRA #
SRB ### ## ## ## ## ##.



###
##, ## # ##, ##
##, ##, ## # ## ##

#####.



BLK

##:
##, ###, ##, ##, ##, ###, ## # ##, ##

##:
##, ## ##, ### ##, ### ## ##, ## #####

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#### ## ##, ##			
	##: ### ##	mg/cm²/h	1.1	≥ 0.8
	##: ### ##	mg/cm²	23	≥ 15
## ##	####			
	##: ### ##	mg/cm²/h	2.4	≥ 2
	##: ### ##	mg/cm²	23	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	PU/##			
	### #####(## ##)	mm³	91	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.41	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.37	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.28	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.25	≥ 0.22
	### ## #	###	11.2	0.1 - 1000
	ESD #	###	54	0.1 - 100
	#### ## ##	J	37	≥ 20
Top	##			
	#### ## #(## # ##### 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## #(## # ## ## 200J)	mm	16.5	≥ 14
	#### ## #(## # ## ## 15kN)	mm	20.0	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com