

Medium

BESTBOY231 S3

###

Safety Jogger BESTBOY231 ##### ## ##, ## ##, ## ##, ##
#####. # ### ##### ## ## ### #####

#####.

## ##	## ##### ##
## ##	##
###	SJ # ##
##	##
###	### PU/### PU
Top	##
####	S3 / SRC
## ##	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
## ##	0.655 kg
###	ASTM F2413:2018 EN ISO 20345:2011



BLK




####.



SRC

#####. SRC ### ## ###
SRA #
SRB ### ##### ## #####.



```
## ###
## ## ## ##### ##### ## ## ##
## ##### ##### ## ## ##
##### ## #####.
```



```
## ### ##
## ## ##### ### ## ## ##
#####.
```



#####.



```
## ##
##### ### ##### ##### ## #####
### ## ###.
```

##:
###, ##, ##, ##, ## # ##, ##, ## # ##, ##

##:
##, ### ##, ## ##### ##, ### ##, ### ## ##, ### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##### ##			
	##: ### ##	mg/cm²/h	2.2	≥ 0.8
	##: ### ##	mg/cm²	25	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	49.8	≥ 2
	##: ### ##	mg/cm²	398.8	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	### PU/### PU			
	### #####(## ##)	mm³	56.4	≤ 150
	### ## ## SRA: ###	##	0.37	≥ 0.28
	## SRA# ### ##: ##	##	0.34	≥ 0.32
	### ## ### SRB: ###	##	0.14	≥ 0.13
	## SRB# ### ##: ##	##	0.18	≥ 0.18
	### ## #	###	120.7	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## #	J	29	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	15	≥ 14
	#### ## # (## # ## ## 15kN)	mm	15	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com