

SAFETY JOGGER

INDUSTRIAL

Medium

BESTBOY METALFREE S3 S3S

BESTBOYMF

All-time favorite mid-cut safety shoe in metal-free execution

The Safety Jogger BESTBOY METALFREE is a versatile, lightweight, metal-free, mid-cut safety shoe with superior features like breathable leather uppers, slip resistance, and S3 rating for high humidity and oil-filled environments.

| | |
|------------|---|
| Upper | Barton Action Leather |
| Lining | Mesh |
| Footbed | SJ foam footbed |
| Midsole | Anti-puncture Textile |
| Outsole | PU/PU |
| Toecap | Composite |
| Category | S3S / SR, LG, ESD, FO |
| Size range | EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315 |
| Norms | ASTM F2413:2018 EN ISO 20345:2022 |



BLK



Oil & fuel resistant

The outsole is resistant against oil and fuel.



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



Slip resistance (SR)

Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.




Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Puncture resistant lightweight

Metal free, super flexible and ultralight puncture resistant midsole. Covers 100% of the bottom area of the last, no thermal conductivity.



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.

Industries:

Assembly, Automotive, Construction, Industry, Logistics

Environments:

Dry environment, Extreme slippery surfaces, Muddy environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|-------------|--------------|
| Upper | Barton Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 2.2 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 25 | ≥ 15 |
| Lining | Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 49.8 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 398.8 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | 25600/12800 | 25600/12800 |
| Outsole | PU/PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 56.4 | ≤ 150 |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | friction | 0.44 | ≥ 0.31 |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | friction | 0.41 | ≥ 0.36 |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | friction | 0.29 | ≥ 0.19 |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction | 0.29 | ≥ 0.22 |
| | Antistatic value | MegaOhm | 96.7 | 0.1 - 1000 |
| | ESD value | MegaOhm | N/A | 0.1 - 100 |
| | Heel energy absorption | J | 26 | ≥ 20 |
| Toecap | Composite | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 17.0 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 22.5 | ≥ 14 |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.