

Medium

BESTBOY METALFREE S3 S3S

BESTBOYMF

##

(Safety Jogger)# #### ## ##, #### ##, #### #### ## ####
S3 ## # #### #### ## #### ## ##### #####.

## ##	## ##### ##
## ##	##
###	SJ # ##
##	## ## ##
###	### PU/### PU
Top	##
####	S3S / SR, SC, LG, ESD, CI, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
###	ASTM F2413:2018 EN ISO 20345:2022+A1:2024



BLK



#####.



S3
S3 #####
#####.

#####.
#####.




##(SR)
SRA+SRB=SRC ###
#####. SR# ### ##### ### ##
#####.



####.



```
## ## ##
### ## ## ##### ##### ## ## ###.
### ## ### 100% ## ## #####
####.
```



```
## ##
### ## ##### ##### ## #####
#####. ## ## ##### ### ## #
##### ## ##### ## #####.
```

##:
####, ###, ##, ##, ##

##:
##, ## ##### ##, ### ##, ### ## ##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##### ##			
	##: ### ##	mg/cm²/h	2.2	≥ 0.8
	##: ### ##	mg/cm²	25	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	49.8	≥ 2
	##: ### ##	mg/cm²	398.8	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	### PU/### PU			
	### #####(## ##)	mm³	56.4	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.41	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.39	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.28	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.27	≥ 0.22
	### ## #	###	32.6	0.1 - 1000
	ESD #	###	29	0.1 - 100
	#### ## ##	J	26	≥ 20
Top	##			
	#### ## #(## # ##### 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## #(## # ## ## 200J)	mm	17.0	≥ 14
	#### ## #(## # ## ## 15kN)	mm	22.5	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com