



Heavy

BESTLIGHT1 OB

###,## ###
BESTLIGHT1 ### ### ### ###. ### ### # # ###
30°C## ##, ### # ## ###.

## ##	### EVA
## ##	N/A
###	SJ ### 2
###	EVA / ##
####	OB / SRC
## ##	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
## ##	0.197 kg
###	EN ISO 20347:2012



BLK



WHT



30°C## ## ##
30°C# #### ## # ##.



##.

##:
####, ##, ##, ## # ##, ##

##:
##, ## ##### ##, ## ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20347
## ##	### EVA			
	##: ### ##	mg/cm²/h	N/A	≥ 0.8
	##: ### ##	mg/cm²	N/A	≥ 15
## ##	N/A			
	##: ### ##	mg/cm²/h	N/A	≥ 2
	##: ### ##	mg/cm²	N/A	≥ 20
###	SJ ### 2			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	EVA / ##			
	### #####(## ##)	mm³	83.0	≤ 150
	### ## ## SRA: ###	##	0.45	≥ 0.28
	## SRA# ### ##: ##	##	0.46	≥ 0.32
	### ## ## SRB: ###	##	0.22	≥ 0.13
	## SRB# ### ##: ##	##	0.32	≥ 0.18
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## #	J	N/A	≥ 20

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ## # #####.