

Medium

BESTRUN S3

#####

Safety Jogger #####
 ### ##, ### ## # ## ## ## ##.

## ##	## ##### ##
## ##	##
###	SJ # ##
##	##
###	PU / PU
Top	##
#####	S3 / SR, SC, LG, CI, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.665 kg
###	ASTM F2413:2018 EN ISO 20345:2022+A1:2024



BLK



S3

```
S3 ##### ## ## ##### #####
## ##### ##### # #####. # ###
## ### ## ##### ## ## #####
#####.
```



```
## ##
##### ## ##### ## ##
### ## ##.
```



```
## ##
## ## ## ##### ## ## ##
## ## ## ## ## ## ##
##### ## #####.
```



#####.



#####.



SRC

#####. SRC ### ## ###
SRA #
SRB ### ##### ## #####.

##:
###, ##, ##, ##, ##, ###, ## # ##, ##

##:
##, ### ##, ### ## ##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##### ##			
	##: ### ##	mg/cm²/h	2.2	≥ 0.8
	##: ### ##	mg/cm²	25	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	49.8	≥ 2
	##: ### ##	mg/cm²	398.8	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	56.4	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.44	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.41	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.29	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.29	≥ 0.22
	### ## #	###	120.7	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	29	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	15	≥ 14
	#### ## # (## # ## ## 15kN)	mm	15	≥ 14

##.

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com