



**SAFETY
JOGGER**
INDUSTRIAL



Medium

BESTRUN231 S3

#####

Safety Jogger BESTRUN231#

#####


##	##
##	##
##	SJ #
##	##
###	### PU/### PU
Top	##
####	S3 / SRC
##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
##	0.620 kg
###	ASTM F2413:2018 EN ISO 20345:2011



BLK




#####



#####



#####



#####



#####



SRC

SRC
SRA #
SRB #####

**SAFETY
JOGGER**
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
###, ####, ##, ##, ##, ## # ##, ##, ## # ##, ##

##:
##, ### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##### ##			
	##: ### ##	mg/cm²/h	2.2	≥ 0.8
	##: ### ##	mg/cm²	25	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	49.8	≥ 2
	##: ### ##	mg/cm²	398.8	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	### PU/### PU			
	### #####(## ##)	mm³	56.4	≤ 150
	### ## ## SRA: ###	##	0.37	≥ 0.28
	## SRA# ### ##: ##	##	0.34	≥ 0.32
	### ## ## SRB: ###	##	0.14	≥ 0.13
	## SRB# ### ##: ##	##	0.18	≥ 0.18
	### ## #	###	120.7	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## #	J	29	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	15	≥ 14
	#### ## # (## # ## ## 15kN)	mm	15	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com