



SAFETY JOGGER

INDUSTRIAL



Medium

BESTZIP S3

###

Safety Jogger ##### ## #### #####. ### SR ### ## ##, ##
##, ### ## #####. ### #### #####.

## ##	## ##### ##
## ##	##
###	SJ # ##
##	##
###	PU / PU
Top	##
####	S3 / SRC
## ##	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
## ##	0.725 kg
###	ASTM F2413:2018 EN ISO 20345:2011



##(WRU)

#####.



S3

S3 ##### ## ## ## ## ##
##. # ##

#####.



SRC

#####. SRC ## ## ##
SRA #
SRB ## ## ## ## ## ##.



BRN

SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
##, ##, ##, ##

##:
##, ### ## ##, ## ##, ###

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##### ##			
	##: ### ##	mg/cm²/h	6.92	≥ 0.8
	##: ### ##	mg/cm²	59	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	47.9	≥ 2
	##: ### ##	mg/cm²	384	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	57	≤ 150
	### ## ## SRA: ###	##	0.35	≥ 0.28
	## SRA# ### ##: ##	##	0.34	≥ 0.32
	### ## ## SRB: ###	##	0.18	≥ 0.13
	## SRB# ### ##: ##	##	0.24	≥ 0.18
	### ## #	###	15.6	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	36	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	17.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	21.5	≥ 14
### ##:				
##### ## ##### ##### ##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## # #####.				