



BOTANIC S1P MID

##, ##, ### # ### ### ## ### ## S1P ### ## ## ##,
#, ESD # # ### ### #### ## #####. #### ## # ##
#####.

## ##	#### ##, ### ##
## ##	##
###	SJ # ##
##	##
####	PU / PU
Top	##
#####	S1P / SR, SC, LG, ESD, CI, FO
## ##	EU 35-43
## ##	0.540 kg
###	EN ISO 20345:2022+A1:2024
	ASTM F2413:2024



```
## ##(LG)
#### ## # ## # ##### #### ## #####
# #### ##### #### #### #####.
```



#####



#####.



```
### ##(SR)
### ##### SRA+SRB=SRC ###
#####. SR# ### ##### ### ##
## ## ##### #####.

```



```
## ###
## ## ## ##### ##### ## ## ###
## ### ##### ##### ### ### ##
##### ## #####.
```



###.

##:
####, ###, ## # ##, ##, ##

##:
##, ## ##### ##, ### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#### ##, ### ##			
	##: ### ##	mg/cm²/h	3.3	≥ 0.8
	##: ### ##	mg/cm²	27.3	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	49.8	≥ 2
	##: ### ##	mg/cm²	398.8	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	PU / PU			
	### ####(## ##)	mm³	135.4	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.39	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.38	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.26	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.29	≥ 0.22
	### ## #	###	200	0.1 - 1000
	ESD #	###	21.2	0.1 - 100
	#### ## ##	J	25	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	15.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	19.5	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com