

BSTKNITS1P


###

```
##, ##, ### # ##### ##### ## ##### S1P ##, ESD ##, ### ## #
### ## # ## #####. ##### ## ##### ## ##### ## #
### ##### ## #####.
```

## ##	TPU, ##
## ##	##
###	SJ # ##
##	##
###	PU / PU
Top	##
#####	S1P / SR, LG, ESD, FO
## ##	EU 35-43 / UK 3.0-9.0 / US 5.5-11.5 JPN 21.5-27 / KOR 230-280
## ##	0.470 kg
###	ASTM F2413:2018 EN ISO 20345:2022+A1:2024



LBL



#####.



```
## ##(LG)
#### ## # ## # ##### #### ## #####
# #### ##### ### ### #####.
```



S1P


##, ## ##, ### # ##
#####? ##### S1P #####
#####.



SJ FOAM
 #####
 #####
 ##



```
### ##
ESD# ## ### ##### # ## ###
##### ### ##### ##### ## ##
### #####. ## ### 100#####
100### #####.
```



#####.

##:
####, ###, ##, ##

##:
##, ## #####

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	TPU, ##			
	##: ### ##	mg/cm²/h	11.2	≥ 0.8
	##: ### ##	mg/cm²	90.0	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	11.7	≥ 2
	##: ### ##	mg/cm²	94.2	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	29.9	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.40	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.43	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.20	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.27	≥ 0.22
	### ## #	###	13.2	0.1 - 1000
	ESD #	###	18	0.1 - 100
	#### ## ##	J	31	≥ 20
	##			
Top	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	15.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	20.5	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com