

Medium

BESTRUN MF EH SB

BSTRUNMFEH

EH ##### ## ## ##

Safety Jogger ##### ## ## EH ##### ## ##### ## #####
#####. ## # ### ##, ## ## # ## ## #####.

## ##	## ##### ##
## ##	##
###	SJ # ##
##	## ## ##
###	### PU/### PU
Top	##
#####	SB / PS, SR, SC, WPA, LG, E, CI, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.655 kg
###	ASTM F2413:2018 EN ISO 20345:2022+A1:2024




BLK



#####.



```
### ## ##
## ### ### ### ### # ## #####
## ## ##### #####.
```



```
## ##
### ## ##### ## #####
#####. ## ## ##### ## ##
##### ## ##### ## #####.
```



```
### ##(EH)
## ##(EH)# ## ##### ##### ###
#####. 2# ## ##### ### ##### ##
### #####.
```



SRC

#####. SRC ### ## ###
SRA #
SRB ### ##### ## #####.

##:
###, ##, ##, ##, ##, ###, ## # ##, ##

##:
##, ### ##, ### ##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##### ##			
	##: ### ##	mg/cm²/h	1.97	≥ 0.8
	##: ### ##	mg/cm²	20	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	86.31	≥ 2
	##: ### ##	mg/cm²	691	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	### PU/### PU			
	### #####(## ##)	mm³	33	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.39	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.37	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.28	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.27	≥ 0.22
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	26	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	15.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	23.0	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com