

CADORS3LOW

S3 ESD

#####

## ##	## ##
## ##	3D ##
###	SJ # ##
##	##
###	PU / PU
Top	##
#####	S3 / SR, SC, ESD, FO
## ##	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
## ##	0.601 kg
###	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



BLK



S3

S3 #####

#####. #

#####.




###

```
## ## ## ##### ##### ## ## ##
## ##### ##### ##### ## ## ##
##### ## #####.
```



##

#####



##

#####.



##

```
ESD# ## ### ##### # ## ###
##### ### ##### ##### ## ##
### #####. ## ### 100#####
100### #####.
```

**SRC**

```
### ## ### ## # ##### ## ###
## # #####. SRC ### ## ###
### ## ## ##### ##### SRA #
SRB ### ##### ## #####.
```

##:
###, ####, ## # ##, ##, ##

##:
##, ## ##, ## ##### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##			
	##: ### ##	mg/cm²/h	2.2	≥ 0.8
	##: ### ##	mg/cm²	28	≥ 15
## ##	3D ##			
	##: ### ##	mg/cm²/h	61.1	≥ 2
	##: ### ##	mg/cm²	490	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	59	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.36	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.42	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.21	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.25	≥ 0.22
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	79	0.1 - 100
	#### ## ##	J	24	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	17.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	20.0	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace
INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com