



SAFETY JOGGER

INDUSTRIAL



Medium


CADOR S3 MID TLS

CADORS3MTL

S3 ESD

TLS #### ## ## ## S3 ####. ## #### ##, ESD ##, SRC #### ##
####, #### # #### #### ## ## ## ## ##
##. ## #### ## ## ## ## ## ## ## ##.

## ##	## ##
## ##	3D ##
###	SJ # ##
##	##
###	PU / PU
Top	##
####	S3 / SR, SC, ESD, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.613 kg
###	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



##.



##.



TLS(#### ## ##)
Safety Jogger # #### TLS ##

#####. ### ## ## TLS #### ##
##. ##
##.



##.



ESD# ## ## ## ## ## ## ##

100#####
100#### ## ##.



SRC

#####. SRC ## ## ##
SRA #
SRB ### ## ## ## ##.

SAFETY JOGGER

WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
####, ###, ## # ##, ##, ##

##:
##, ## ##, ## ##### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##			
	##: ### ##	mg/cm²/h	2.2	≥ 0.8
	##: ### ##	mg/cm²	28	≥ 15
## ##	3D ##			
	##: ### ##	mg/cm²/h	61.1	≥ 2
	##: ### ##	mg/cm²	490	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	59	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.36	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.42	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.21	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.25	≥ 0.22
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	79	0.1 - 100
	#### ## ##	J	24	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	17.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	20.0	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## # #####.



Solutions for every workplace
INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com