



SAFETY JOGGER INDUSTRIAL



Medium

CADOR S3 LOW TLS

CADORS3TLS

TLS(#### # ###)# ### ##### ### ESD ###

TLS ##### # S3 ###. ## #####, ESD ##, SRC #####


##. ## ##### # ##### # #####.

## #	## #
## #	3D #
###	SJ #
##	##
###	PU / PU
Top	##
####	S3 / SR, SC, ESD, FO
## #	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## #	0.580 kg
###	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



S3
S3 #####
#####. # ##

#####.



#####.



TLS(#### # ###)
Safety Jogger ##### TLS ##
#####. ##
#, # #####
#####. ## ##### TLS #####
#####. ##
#####.



ESD# ## ##### # ##

#####. ## # 100#####
100### #####.



SRC

#####. SRC # # #
SRA #
SRB # # # # #.



#####.

SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
####, ###, ## # ##, ##, ##

##:
##, ## ##### ##, ## ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##			
	##: ### ##	mg/cm²/h	2.2	≥ 0.8
	##: ### ##	mg/cm²	28	≥ 15
## ##	3D ##			
	##: ### ##	mg/cm²/h	61.1	≥ 2
	##: ### ##	mg/cm²	490	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	59	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.36	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.42	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.21	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.25	≥ 0.22
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	79	0.1 - 100
	#### ## ##	J	24	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	17.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	20.0	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace
INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com