



SAFETY JOGGER

INDUSTRIAL



#

CADOR S1P SANDAL

CADORSNDL


ESD ##

CADOR S1P# #### ## ##, ESD ##, #### ## ##, ## ## ##### ## ####
 ## #####. #### ##### ##### ##### #####.

## ##	##
## ##	3D ##
###	SJ # ##
##	##
###	PU / PU
Top	##
#####	S1 P / SR, ESD, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.627 kg
###	ASTM F2413:2018 EN ISO 20345:2022



GRY



 ## # ## ## ##### ## ##### ##
 ##### ## ##### ##.



SRC
 ### ## ## ## ## ## ## ## ##
 ## # #####. SRC ### ## ##
 ### ## ## ## ## ## ## SRA #
 SRB ### ## ## ## ## ##.



 ## ## ## ## ## ## ## ## ##
 ## ## ## ## ## ## ## ## ##
 ##### ## ## ##.



 ##### ## ## ## ## ## ## ##
 ### ## ## ##.



 ### ## ## ## ## ## ## ##
 ##### ## ## ##.



 ESD# ## ## ## ## ## ##
 ##### ## ## ## ## ## ##
 ### ## ## ## ## ## 100#####
 100### ## ##.

SAFETY JOGGER
 WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
 IN EUROPE

www.safetyjogger.com

##:
####, ###, ##, ##

##:
##

##:
#####. ### ##### ## ##### ### ##.

	##	## ##	##	EN ISO 20345
## ##	##			
	##: ### ##	mg/cm²/h	3.9	≥ 0.8
	##: ### ##	mg/cm²	41	≥ 15
## ##	3D ##			
	##: ### ##	mg/cm²/h	61.1	≥ 2
	##: ### ##	mg/cm²	490	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	59	≤ 150
	### ## ## SRA: ###	##	0.30	≥ 0.28
	## SRA# ### ##: ##	##	0.39	≥ 0.32
	### ## ## SRB: ###	##	0.15	≥ 0.13
	## SRB# ### ##: ##	##	0.24	≥ 0.18
	### ## #	###	8.1	0.1 - 1000
	ESD #	###	73	0.1 - 100
	#### ## #	J	24	≥ 20
Top	##			
	#### ## #(## # ##### 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## #(## # ## ## 200J)	mm	15.0	≥ 14
	#### ## #(## # ## ## 15kN)	mm	19.0	≥ 14

##:
###, ## ## ##### ## # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ### ## ##### ##### ### # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com