

Medium

DAKAR S3

#####

```
Safety Jogger DAKAR# ### ## # #####. ## ## ##### #####.
## ## ## ## ## ## ## ## ##### # ## ## ## ## #####.
S3 ##. ## ##. ## ## ##### ##### ## #####.
```

## ##	##,#### ## ##
## ##	##
###	SJ # ##
##	##
###	PU / PU
Top	##
#####	S3 / SR, SC, CI, FO
## ##	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
## ##	0.710 kg
###	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



070



018

019

**SRC**

```
### ## ### ### # ##### ## ###
## # #####. SRC ### ## ###
### ### ## ##### ##### SRA #
SRB ### ##### ## #####.
```



S3

S3 #####

#####



###

#####



##

```
### ## ### ##### ### ##### ###
### #####. 100##### 1### ##
## ##
```



###

#####.



SJ FOAM

#####.

##:

###, ##, ##, ## # ##, ##

##:

##, ### ## ##, ##

##:

#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	##, ##### ## ##			
	##: ### ##	mg/cm²/h	7.8	≥ 0.8
	##: ### ##	mg/cm²	68	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	46.42	≥ 2
	##: ### ##	mg/cm²	372	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	88	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.38	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.45	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.34	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.31	≥ 0.22
	### ## #	###	21.7	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	28	≥ 20
Top	##			
	#### ## #(## # ##### 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## #(## # ## ## 200J)	mm	17.5	≥ 14
	#### ## #(## # ## ## 15kN)	mm	21.5	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.