

Medium

DAKAR EW S3

DAKAREWS3

##, ## # ## ## ## 2## DAKAR #####.

DAKAR EW S3# #### #### ### ####, ## ## ## #### ##
####. ### #### #### #### #### ## ## ####
####. S3 ### #### #### ## # ## #### ####.

## ##	##, #### ## ##
## ##	##
###	SJ # ##
##	##
###	### PU/### PU
Top	##
####	S3 / SR, SC, LG, CI, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.703 kg
###	ASTM F2413:2018 EN ISO 20345:2022+A1:2024



BLK



BRN



#####.



```
## ##(LG)
### ## # ## # ##### ### ##
# ### ##### ### ### #####.
```



#####.



S3
S3 ##### ## #####
#####. # ##

#####.



```
### #(SC)
### ## # # ## ### ### ### ###
##### ## ## ### ## ## ##
##### ## ### #####.
```



SJ FOAM

#####.

##:

##, ##

##:

##, ### ##, ##

##:

#####. ### ##### ## ##### ### ##.

##	## ##	##	EN ISO 20345
## ##	##, ##### ## ##		
	##: ### ##	mg/cm²/h	68 ≥ 0.8
	##: ### ##	mg/cm²	7.8 ≥ 15
## ##	##		
	##: ### ##	mg/cm²/h	46.42 ≥ 2
	##: ### ##	mg/cm²	372 ≥ 20
###	SJ # ##		
	###: #####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles25600/12800
###	### PU/### PU		
	### #####(## ##)	mm³	50 ≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.46 ≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.45 ≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.35 ≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.34 ≥ 0.22
	### ## #	###	50.5 0.1 - 1000
	ESD #	###	N/A 0.1 - 100
	#### ## ##	J	41 ≥ 20
Top	##		
	#### ## # (## # ##### 100J)	mm	N/A N/A
	#### ## # (## # ## ## 10kN)	mm	N/A N/A
	#### ## # (## # ## ## 200J)	mm	20.5 ≥ 14
	#### ## # (## # ## ## 15kN)	mm	22.0 ≥ 14

##:

##, ## ## ##### ### # #####. ## ##### ### Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ### # #####.