

Medium

DAKAR EW S3

DAKAREWS3

##, ### # ##### ## 2## DAKAR #####.

DAKAR EW S3# #### #### ### ####, ## ## ## #### ##
####, ### #### #### #### #### ## ## ####
####. S3 ### #### #### ## # ## #### ####.

## ##	##, #### ## ##
## ##	##
###	SJ # ##
##	##
###	### PU/### PU
Top	##
####	S3 / SR, SC, LG, CI, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.703 kg
###	ASTM F2413:2018 EN ISO 20345:2022+A1:2024



BRN



BLK



#####.



```
## ##(LG)
#### ## # ## # ##### #### ## #####
# #### ##### #### #### #####.
```



#####.



S3
S3 ##### ## #####
#####. # ##

#####.



```
### #(SC)
### ## # # ## ### ### ### ###
#### ##### ## ## ### ## ## ###
#### ## ### #####.
```



SJ FOAM

#####.

## ##: ##, ## ## ##: ### ##, ### ##, ## ## ## ## ##: ### ### ##### ##### ### ##### ### ##### ## #####. ### ##### ## ##### ### ##.				
##	## ##	##	EN ISO 20345	
## ##	##, ##### ## ##			
	##: ### ##	mg/cm²/h	68	≥ 0.8
	##: ### ##	mg/cm²	7.8	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	46.42	≥ 2
	##: ### ##	mg/cm²	372	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	### PU/### PU			
	### #####(## ##)	mm³	50	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.46	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.45	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.35	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.34	≥ 0.22
	### ## #	###	50.5	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	41	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	20.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	22.0	≥ 14

##:

#####. ## ##### ### Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.