



#

DESERT S1 P

#####

##, ##, ## ## ## ##, ## ##, ### ##, ## ##, ## ##, ## ##,
##, ## #, S1P PU

## ##	##
## ##	##
###	SJ # ##
##	##
###	PU / PU
Top	##
####	S1 P / SRC
## ##	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
## ##	0.710 kg
###	ASTM F2413:2018 EN ISO 20345:2011



043



011



117



MUL



SJ FOAM

#, ### # ## ##
#####. ### # ## ##.

SRC

#####. SRC ## ## ##
SRA #
SRB ## ## ## ## ##.

##

##.

##

#####.

####

#####. 100##### 1#### ##
##

SJ-3-Fit

Safety Jogger ## ## ## ## ##
##.

##:
###, ##, ##, ##

##:
##, ### ##

##:
#####. ### ##### ## ##### ### ##.

	##	## ##	##	EN ISO 20345
## ##	##			
	##: ### ##	mg/cm²/h	3.3	≥ 0.8
	##: ### ##	mg/cm²	31.6	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	17.2	≥ 2
	##: ### ##	mg/cm²	140.7	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	46	≤ 150
	### ## ## SRA: ###	##	0.32	≥ 0.28
	## SRA# ### ##: ##	##	0.32	≥ 0.32
	### ## ## SRB: ###	##	0.16	≥ 0.13
	## SRB# ### ##: ##	##	0.18	≥ 0.18
	### ## #	###	123.7	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	34	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	16	≥ 14
	#### ## # (## # ## ## 15kN)	mm	19	≥ 14

##:
###, ## ## ##### ## # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ### ## ##### ##### ### # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com