



#

## DESERT S1 P

#####

### ##, ##, ## ## ## ##, ## ##, ### ##, ## ##, ## ##, ## ##,  
### ##, ## #, S1P PU ##

|       |                                                                   |
|-------|-------------------------------------------------------------------|
| ## ## | ##                                                                |
| ## ## | ##                                                                |
| ###   | SJ # ##                                                           |
| ##    | ##                                                                |
| ###   | PU / PU                                                           |
| Top   | ##                                                                |
| ####  | S1 P / SRC                                                        |
| ## ## | EU 36-47 / UK 3.5-12.0 / US 4.0-13.0<br>JPN 22.5-31 / KOR 235-310 |
| ## ## | 0.710 kg                                                          |
| ###   | ASTM F2413:2018<br>EN ISO 20345:2011                              |



MUL



011



043



117



### SJ FOAM

#####  
##### ## #, ### # ## ##  
## ### #####. ### # ## ##.

### SRC

#### ## ## ## # #### ## ##  
## # #####. SRC #### ## ##  
#### ## ##### SRA #  
SRB #### ## #####.

### ## ##

#####  
#####  
### ## ##.

### ## ##

## ## ## ## ## ## ## ## ##  
## ## ## ## ## ## ## ## ##  
#####.

### ####

#### ## ## ## ## ## ## ## ##  
#####. 100##### 1#### ##  
## ##

### SJ-3-Fit

Safety Jogger #### ## ## ## ##  
## #####  
#####.

## ##:  
###, ##, ##, ##

## ##:  
### ##, ### ## ##

## ## ##:  
### ### ##### ##### ## ##### ## ##### ## #####. ### ##### ## ##### ## ##.

|       | ##                          | ## ##    | ##          | EN ISO 20345 |
|-------|-----------------------------|----------|-------------|--------------|
| ## ## | ##                          |          |             |              |
|       | ##: ### ##                  | mg/cm²/h | 3.3         | ≥ 0.8        |
|       | ##: ### ##                  | mg/cm²   | 31.6        | ≥ 15         |
| ## ## | ##                          |          |             |              |
|       | ##: ### ##                  | mg/cm²/h | 17.2        | ≥ 2          |
|       | ##: ### ##                  | mg/cm²   | 140.7       | ≥ 20         |
| ###   | SJ # ##                     |          |             |              |
|       | ###: #####(##/##)(###)      | ##       | 25600/12800 | 25600/12800  |
| ###   | PU / PU                     |          |             |              |
|       | ### #####(## ##)            | mm³      | 46          | ≤ 150        |
|       | ### ## ## SRA: ###          | ##       | 0.32        | ≥ 0.28       |
|       | ## SRA# ### ##: ##          | ##       | 0.32        | ≥ 0.32       |
|       | ### ## ## SRB: ###          | ##       | 0.16        | ≥ 0.13       |
|       | ## SRB# ### ##: ##          | ##       | 0.18        | ≥ 0.18       |
|       | ### ## #                    | ###      | 123.7       | 0.1 - 1000   |
|       | ESD #                       | ###      | N/A         | 0.1 - 100    |
|       | #### ## ##                  | J        | 34          | ≥ 20         |
| Top   | ##                          |          |             |              |
|       | #### ## # (## # ##### 100J) | mm       | N/A         | N/A          |
|       | #### ## # (## # ## ## 10kN) | mm       | N/A         | N/A          |
|       | #### ## # (## # ## ## 200J) | mm       | 16          | ≥ 14         |
|       | #### ## # (## # ## ## 15kN) | mm       | 19          | ≥ 14         |

### ##:  
##### ### ##### ##, ## ## ##### ## # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ##### ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL   PROFESSIONAL   TACTICAL   TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com