



Medium

DUNE OB

##

####. ## ## #### ## ####
####. ## ##, #, # ## ## ##
####. ## ## ## ## ## ## ####.

## ##	#### ##, ##
## ##	##
###	SJ # ##
###	##
####	OB / SR, LG, E, ##, CI, FO, HRO
## ##	EU 38-48 / UK 5.0-13.0 / US 5.5-13.5 JPN 24-31.5 / KOR 250-315
## ##	0.710 kg
###	EN ISO 20347:2022+A1:2024 ASTM F3445:2024



####.

SRC

####. SRC ### ## ####
SRA #
SRB ### #### ## ####.

SJ FOAM

##, ## # ## ##
####. ## # ## ##.

####, ## # ##, ##
##, ## # ## ##


####.

#####. 100##### 1### ##
##

##.



SND



##:
##

##:
##, ### ##

##:
#####. #### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20347
## ##	#### ##, ##			
	##: ### ##	mg/cm²/h	4.5	≥ 0.8
	##: ### ##	mg/cm²	35	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	45	≥ 2
	##: ### ##	mg/cm²	350	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	##			
	### #####(## ##)	mm³	85	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.33	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.37	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	N/A	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	N/A	≥ 0.22
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	N/A	≥ 20

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.