



**SAFETY
JOGGER**
INDUSTRIAL



#

ECODESERT S1P MID

ECODESERT

#####

###	###
###	###
###	SJ #
##	##
###	PU / PU
Top	##
####	S1 P / SR, FO
###	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
##	0.662 kg
###	ASTM F2413:2018 EN ISO 20345:2022



KHA



AH6



BLK



SRC

SRC #####
SRA #
SRB #####



SJ-3-FIT

#####



SJ-3-FIT

#####



SJ-3-FIT

100##### 1#####
###



SJ-3-FIT

#####



SJ-3-FIT

Safety Jogger #####
#####

**SAFETY
JOGGER**
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

##:
###, ##, ##, ##

##:
##, ###

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	### ##			
	##: ### ##	mg/cm²/h	7.1	≥ 0.8
	##: ### ##	mg/cm²	57.5	≥ 15
## ##	### ##			
	##: ### ##	mg/cm²/h	10.7	≥ 2
	##: ### ##	mg/cm²	87.8	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	Relative volume loss:0.9g/cm³(Density:0.98)	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.48	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.49	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.21	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.24	≥ 0.22
	### ## #	###	26.5	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	40	≥ 20
Top	##			
	#### ## #(## # ##### 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## #(## # ## ## 200J)	mm	17.5	≥ 14
	#### ## #(## # ## ## 15kN)	mm	23.0	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com