

##:
####, ##, ##, ##

##:
##, ###

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#####,### ##			
	##: ### ##	mg/cm²/h	1.2	≥ 0.8
	##: ### ##	mg/cm²	21	≥ 15
## ##	### ##			
	##: ### ##	mg/cm²/h	34.59	≥ 2
	##: ### ##	mg/cm²	277	≥ 20
###	SJ ### # ###			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	###/##			
	### ####(## ##)	mm³	119.4mm³(Density:1.3)	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.48	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.48	≥ 0.36
	SR ## ## - ## + #### - ##### ## ##	##	0.36	≥ 0.19
	SR ## ## - ## + #### - ## ## ##	##	0.36	≥ 0.22
	### ## #	###	648	0.1 - 1000
	ESD #	###	19.4	0.1 - 100
	#### ## ##	J	25	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	NA	N/A
	#### ## # (## # ## ## 10kN)	mm	NA	N/A
	#### ## # (## # ## ## 200J)	mm	15.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	22.0	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com