



SAFETY JOGGER

PROFESSIONAL



Medium

ELIS 02

#####

Elis O2# ##### ## ##### ## ## #, SR ### #, ESD
#####.

## #	Lorica
## #	3D #
###	SJ #
###	#####
####	O2 / ESD, SRC
## #	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
## #	0.220 kg
###	ASTM F2892:2018 EN ISO 20347:2012



BLK



WHT



3D #

#####.




ESD# ## ## ## #

#####. # ## 100#####
100### #####.



#####.




/ SJ #
© ## ## ## #

SRC(SRA+ SRB) ## #####.



#####.



#####.

##:
####, ##, ##

##:
##, ## #### ##, ## ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20347
## ##	Lorica			
	##: ### ##	mg/cm²/h	2.18	≥ 0.8
	##: ### ##	mg/cm²	18	≥ 15
## ##	3D ##			
	##: ### ##	mg/cm²/h	70	≥ 2
	##: ### ##	mg/cm²	350	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	###/##			
	### #####(## ##)	mm³	105	≤ 150
	### ## ## SRA: ###	##	0.44	≥ 0.28
	## SRA# ### ##: ##	##	0.48	≥ 0.32
	### ## ## SRB: ###	##	0.25	≥ 0.13
	## SRB# ### ##: ##	##	0.29	≥ 0.18
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	60	0.1 - 100
	#### ## ##	J	28	≥ 20

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ## ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com