

Medium

EOS S3S

ESD ## ###, ###

Safety Jogger EOS# #### ## ## ## #####. #### ## ### ##### ##
##. ## ### ## ## ##. ##### ### #####.

## ##	## ## ##
## ##	##
###	SJ # ##
##	## ## ##
###	PU / PU
Top	##
#####	S3S / SR, ESD, FO
## ##	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
## ##	0.665 kg
###	ASTM F2413:2018 EN ISO 20345:2022



210



S3

S3 #####

#####. #

#####


**SRC**

```
### ## ### ### # ##### ## ###
## # #####. SRC ### ## ###
### ### ## ##### ##### SRA #
SRB ### ##### ## #####
```



##

```
ESD# ## #### ##### # ## ###
##### ### ##### ##### ## ##
### #####. ## ### 100#####
100### #####.
```




##

```
### ## ##### ##### ## #####
#####. ## ## ##### ## ## #
##### ## ##### ## #####.
```



##

#####.



#####

####.

##:
###, ##, ##, ##, ###, ## # ##, ##

##:
##, ### ##, ### ## ##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ## ##			
	##: ### ##	mg/cm²/h	2.0	≥ 0.8
	##: ### ##	mg/cm²	24.2	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	67.6	≥ 2
	##: ### ##	mg/cm²	541	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	85.1	≤ 150
	### ## ## SRA: ###	##	0.41	≥ 0.28
	## SRA# ### ##: ##	##	0.43	≥ 0.32
	### ## ## SRB: ###	##	0.13	≥ 0.13
	## SRB# ### ##: ##	##	0.19	≥ 0.18
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	24	0.1 - 100
	#### ## ##	J	35	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	16.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	21.5	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ## ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com