



#


FLOW S1P LOW

FLAWS1PL

ESD

Safety Jogger FLOWS1PL# SR ### ##, ### ## ## ## ##, #####
##, ### ##### ## ##### ESD ##### ## ## ## ## ##.

## ##	##
## ##	3D ##
###	SJ # ##
##	## ## ##
###	PU / PU
Top	##
####	S1 P / ESD, SRC
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.590 kg
###	ASTM F2413:2018 EN ISO 20345:2011



##.




SRC

#####. SRC ### ## ## ##
SRA #
SRB ### ## ## ## ## ## ## ##.



ESD# ## ## ## ## ## ## ## ##

#####. ## ## ## 100#####
100### #####.



#####. ## ## ## ## ## ## ## ##
##.



##.



100% ## ## ## ## ##
####.

##:
####, ###, ## # ##, ##, ##

##:

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	##			
	##: ### ##	mg/cm²/h	3.9	≥ 0.8
	##: ### ##	mg/cm²	41	≥ 15
## ##	3D ##			
	##: ### ##	mg/cm²/h	61.1	≥ 2
	##: ### ##	mg/cm²	490	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	84	≤ 150
	### ## ## SRA: ###	##	0.36	≥ 0.28
	## SRA# ### ##: ##	##	0.37	≥ 0.32
	### ## ## SRB: ###	##	0.14	≥ 0.13
	## SRB# ### ##: ##	##	0.19	≥ 0.18
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	39	0.1 - 100
	#### ## ##	J	27	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	15.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	19.0	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com