

Medium

FLOW S3 LOW S3S

FLOWS3LOW

S3 ESD

FLOW S3# ## # ## ## ##### ## ### ## ## #####. ## ## ##, ##
##, ESD, ## ## ## ## # ## ## ## ## ## ##. ## ##
##.

## ##	## ##
## ##	3D ##
###	SJ # ##
##	## ## ##
###	PU / PU
Top	##
####	S3S / SR, SC, ESD, CI, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.600 kg
###	ASTM F2413:2018 EN ISO 20345:2022+A1:2024



BLK



S3
S3 #####
#####.

#####.
#####.



```

SRC
### ## ### ### # ##### ## ###
## # #####. SRC ### ## ###
### ### ## ##### ##### SRA #
SRB ### ##### ## #####.


```



```
### ##
ESD# ## ### ##### # ## ###
##### ### ##### ##### ## ##
### #####. ## ### 100#####
100### #####.
```



```
### ###
### ##### ##### ## ##### ###
##### ## #####.
```



```
##### ##
## # ## ## ##### ## ##### #####
##### ## ## ##### #####.
```



#####.

##:
####, ###, ## # ##, ##, ##

##:
##, ## ##### ##, ## ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##			
	##: ### ##	mg/cm²/h	2.2	≥ 0.8
	##: ### ##	mg/cm²	28	≥ 15
## ##	3D ##			
	##: ### ##	mg/cm²/h	61.1	≥ 2
	##: ### ##	mg/cm²	490	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	84	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.36	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.37	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.24	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.27	≥ 0.22
	### ## #	###	43.3	0.1 - 1000
	ESD #	###	39	0.1 - 100
	#### ## ##	J	26	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	18.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	22.0	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace
INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com