

Medium

FLOW S3 MID S3S

FLOWS3MID

S3 ESD


FLOW S3 #####

#####


## ##	## ##
## ##	3D ##
###	SJ # ##
##	## ## ##
###	PU / PU
Top	##
####	S3S / SR, SC, ESD, CI, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.615 kg
###	ASTM F2413:2018 EN ISO 20345:2022+A1:2024



BLK



```
##### ##
## # ## ## ##### ## ##### #####
##### ### ##### #####.
```



```
###
### ## ##### ## #####
#####. ## ## ##### ## ## #
##### ## ##### ## #####.
```



#####.




```
## ## ##
### ## ## ##### ## ## ##.
### ## ### 100% ## ## #####
####.
```



SRC

#####. SRC ### ## ###
SRA #
SRB ### ##### ## #####.



```
### ##
ESD# ## ### ##### # ## ###
##### ### ##### ##### ## ##
### #####. ## ### 100#####
100### #####.
```

##:
####, ###, ## # ##, ##, ##

##:

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##			
	##: ### ##	mg/cm²/h	2.2	≥ 0.8
	##: ### ##	mg/cm²	28	≥ 15
## ##	3D ##			
	##: ### ##	mg/cm²/h	61	≥ 2
	##: ### ##	mg/cm²	490	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	84	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.36	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.37	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.24	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.27	≥ 0.22
	### ## #	###	43.3	0.1 - 1000
	ESD #	###	39	0.1 - 100
	#### ## ##	J	26	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	18.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	22.0	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com