



SAFETY JOGGER

PROFESSIONAL



#

JAMES OB

##

##, 3D ##, ## ## ## ## ##
#####.

## ##	##
## ##	##
###	SJ # ##
###	#####
####	OB / SRA, E
## ##	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
## ##	0.330 kg
###	ASTM F2892:2024 EN ISO 20347:2012



NAV



BLK



LGR




3D ##

#####.



##

#####. # ## ## ## ##
#####. ## # ##
##.



##

#####.

SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
####, ## # ##, ##

##:
##

##:
#####. ### ##### ## ##### ### ##.

	##	## ##	##	EN ISO 20347
## ##	##			
	##: ### ##	mg/cm²/h	1.4	≥ 0.8
	##: ### ##	mg/cm²	15.5	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	28.9	≥ 2
	##: ### ##	mg/cm²	231.3	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	###/##			
	### #####(## ##)	mm³	81	≤ 150
	### ## ## SRA: ###	##	0.48	≥ 0.28
	## SRA# ### ##: ##	##	0.45	≥ 0.32
	### ## ## SRB: ###	##	N/A	≥ 0.13
	## SRB# ### ##: ##	##	N/A	≥ 0.18
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## #	J	34	≥ 20

##:
###, ## ## ##### ### # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## #### ## ##### ##### ### # #####.