



# SAFETY JOGGER

## PROFESSIONAL



Light

## JUMADI OB

JUMADIOB

**Comfortable, lightweight and ultra breathable occupational trainer with wider toebox**

Safety Jogger's JUMADI OB is a lightweight, ultra-breathable occupational shoe that features superior slip resistance and a removable footbed. Ideal for dry environments in assembly, logistics, medical, or catering industries.

Upper	Mesh
Lining	Mesh
Footbed	SJ foam footbed
Outsole	EVA/Rubber (NBR)
Category	OB / SR, E
Size range	EU 35-48
Sample weight	0.297 kg
Norms	EN ISO 20347:2022+A1:2024



BLK



LBL

PNK

WHT




**Breathable upper**  
Increased moisture and temperature management for extended wearer comfort.



**Slip resistance (SR)**  
Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



**SJ Foam**  
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



**Metal free**  
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



### Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED IN EUROPE

www.safetyjogger.com

**Industries:**

Catering, Medical, Assembly, Logistics

**Environments:**

Dry environment

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Mesh</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	30.55	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	244	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	30.55	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	244	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
<b>Outsole</b>	<b>EVA/Rubber (NBR)</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	60	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.44	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.38	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.24	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.24	≥ 0.22
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
Heel energy absorption	J	34	≥ 20	

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.