



```
###
### ## ##### ##### ## #####
#####. ## ## ##### ### ## #
##### ## ##### ## #####.
```

##:
####, ##, ####, ##

##:
##

	##	## ##	##	EN ISO 20347
## ##	##			
	##: ### ##	mg/cm²/h	30.55	≥ 0.8
	##: ### ##	mg/cm²	244	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	30.55	≥ 2
	##: ### ##	mg/cm²	244	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	EVA / ##			
	### #####(## ##)	mm³	60	≤ 150
	## #### ## - ### + NaLS - ## ####	##	0.44	≥ 0.31
	## #### ## - ### + NaLS - ## ##	##	0.38	≥ 0.36
	SR #### ## - ### + ##### - #####	##	0.24	≥ 0.19
	SR #### ## - ### + ##### - ## ##	##	0.24	≥ 0.22
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ##	J	34	≥ 20

##:
##, ## ## ##### ## # #####. ## ##### Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com