



JUMPER EH SB

JUMPER-EH

EH-rated, low-cut safety shoe with enhanced grip control

Safety Jogger's low-cut JUMPER-EH is an EH-rated, low-cut safety shoe that combines SR slip-resistance, metal-free lightness, electrical hazard protection, and heel energy absorption.

Upper	Suede Leather, Textile
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	PU
Toecap	Composite
Category	SB / P, SRC, E, FO, EH
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.600 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011




117



Electrical hazard (EH)

Electrical hazard (EH) rated safety shoes have nonconductive outsoles. As a secondary source of protection they reduce the potential for electric shocks under dry conditions.



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

Industries:

Automotive, Cleaning, Construction, Food & beverages, Logistics, Medical, Industry

Environments:

Uneven surfaces, Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Suede Leather, Textile			
	Upper: permeability to water vapor	mg/cm ² /h	11.7	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	101.6	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	86.9	≥ 2
	Lining: water vapor coefficient	mg/cm ²	695.4	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU			
	Outsole abrasion resistance (volume loss)	mm ³	186.2	≤ 150
	Outsole slip resistance SRA: heel	friction	0.39	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.34	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.15	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	34	≥ 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	22.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.