



Medium

JUMPER31 S3

#####

##31# ### ##, ## ## # ##### ##### ## ## ## #####. ### ##
#####.

## ##	#### ##
## ##	##
###	SJ # ##
##	## ## ##
###	BASF PU
Top	##
#####	S3 / SRC
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.600 kg
###	ASTM F2413:2024 EN ISO 20345:2011




BLK



S3
S3 ##### ## #####
#####. # ##

#####.



```
## ##
### ## ##### ## #####
#####. ## ## ##### ## ## #
#### ## ##### ## #####.
```



```
## # #
#### ## ##### # ## ## ##### #####
```




SJ ###

#####. # ### # ##### #####. ##
100%# #####.



#####.



```
### ##
### ## ### ##### ### ##### #####
### #####. 100##### 1### ###
## ##
```

##:
###, ##, ##, ##

##:
##, ### ## ##, ## ##, ###

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#### ##			
	##: ### ##	mg/cm²/h	11.4	≥ 0.8
	##: ### ##	mg/cm²	99.8	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	82.9	≥ 2
	##: ### ##	mg/cm²	663.2	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	BASF PU			
	### #####(## ##)	mm³	46	≤ 150
	### ## ## SRA: ###	##	0.32	≥ 0.28
	## SRA# ### ##: ##	##	0.32	≥ 0.32
	### ## ## SRB: ###	##	0.16	≥ 0.13
	## SRB# ### ##: ##	##	0.20	≥ 0.18
	### ## #	###	12.7	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	34	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	16.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	19.0	≥ 14

##:

#####, ## ## ##### ## # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ### ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com