

#

KOMODO S3

#####

#####, #####. #
S3# #####.

##	##, ##
##	##
###	SJ #
##	###
###	###/###
Top	##
####	S3 / ESD, SRC
##	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
##	0.530 kg
###	ASTM F2413:2018 EN ISO 20345:2011



BLK



S3
S3 #####
#####. #

#####.




SRC

#####. SRC #####
SRA #
SRB #####.



ESD
ESD# #####

#####. # 100#####
100#####.



#####. #
#####.



#####. #
#####.



#####.

##:
###, ## # ##, ##, ##, ##, ###

##:
##, ## ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	##, ## ##			
	##: ### ##	mg/cm²/h	3.5	≥ 0.8
	##: ### ##	mg/cm²	33	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	68.4	≥ 2
	##: ### ##	mg/cm²	547	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	###/##			
	### #####(## ##)	mm³	65	≤ 150
	### ## ## SRA: ###	##	0.46	≥ 0.28
	## SRA# ### ##: ##	##	0.39	≥ 0.32
	### ## ## SRB: ###	##	0.14	≥ 0.13
	## SRB# ### ##: ##	##	0.18	≥ 0.18
	### ## #	###	N/A	0.1 - 1000
	ESD #	###	22	0.1 - 100
	#### ## ##	J	21	≥ 20
Top	## ##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	16.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	17.0	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ##### ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com