



SAFETY JOGGER

INDUSTRIAL



Medium

LABOR S3

#####

LABOR# #####. ## ## # # ## ##
##, #, ##, #, ##### ## #####.

##	#####
##	##
###	SJ #
##	##
###	##
Top	##
####	S3 / SR, LG, ##, CI, FO, HRO
##	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
##	0.710 kg
###	EN ISO 20345:2022 ASTM F2413:2024



300°C# ## # # ##.



SRC

#####. SRC ## # #
SRA #
SRB ## # # # # # #.



#####.



SJ FOAM

#, # # # # #
#####. ## # # #.



#.



#####. 100##### 1###
##



BLK

SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
##, ####, ##, ##, ## # ##, ## # ##

##:
##, ## ##### ##, ####

```
## ## ##:
```

##	## ##	##	EN ISO 20345
## ##	## ##### ##		
	##: ### ##	mg/cm²/h	0.92 ≥ 0.8
	##: ### ##	mg/cm²	15.0 ≥ 15
## ##	##		
	##: ### ##	mg/cm²/h	59.9 ≥ 2
	##: ### ##	mg/cm²	480 ≥ 20
###	SJ # ##		
	###: ####(##/##)(###)	##	25600/12800 25600/12800
###	##		
	### #####(## ##)	mm³	92 ≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.40 ≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.42 ≥ 0.36
	SR ## ## - ## + #### - #### ## ##	##	0.32 ≥ 0.19
	SR ## ## - ## + #### - ## ## ##	##	0.34 ≥ 0.22
	### ## #	###	20.5 0.1 - 1000
	ESD #	###	N/A 0.1 - 100
	#### ## ##	J	32.0 ≥ 20
Top	##		
	#### ## # (## # ##### 100J)	mm	N/A N/A
	#### ## # (## # ## ## 10kN)	mm	N/A N/A
	#### ## # (## # ## ## 200J)	mm	19.5 ≥ 14
	#### ## # (## # ## ## 15kN)	mm	22.5 ≥ 14

```
#####
#### #:
#####
##### ## ##### # ####. ## ##### Safety Jogger # ##### ##, ### ## ## ## ##### ##### ## # #####
```