

LAUREN

Light and airy shoe with a adjustable strap

The LAUREN clogs offer exceptional comfort and moisture management. Equipped with an adjustable strap, veganfriendly and suitable for various industries, these shoes combine performance and affordability.

Upper	Mesh, Synthetic
Lining	Mesh
Footbed	Oxy Basic
Outsole	EVA
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 JPN 21.5-26.5 / KOR 230-270
Sample weight	0.140 kg







VI00%

Vegan Uses or contains no animal products.



Breathable upper

Increased moisture and temperature management for extended wearer comfort.



Coolmax[®] lining

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result			
Upper	Mesh, Synthetic					
	Upper: permeability to water vapor	mg/cm²/h	N/A	≥ 0.8		
	Upper: water vapor coefficient	mg/cm ²	N/A	≥ 15		
Lining	Mesh					
	Lining: permeability to water vapor	mg/cm²/h	N/A	≥ 2		
	Lining: water vapor coefficient	mg/cm ²	N/A	≥ 20		
Footbed	Oxy Basic					
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800		
Outsole	EVA					
	Outsole abrasion resistance (volume loss)	mm³	N/A	≤ 150		
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	N/A	≥ 0.31		
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	N/A	≥ 0.36		
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	N/A	≥ 0.19		
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	N/A	≥ 0.22		
	Antistatic value	MegaOhm	N/A	0.1 - 1000		
	ESD value	MegaOhm	N/A	0.1 - 100		
	Heel energy absorption	J	N/A	≥ 20		

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace