



SAFETY JOGGER

INDUSTRIAL



#

LOBI S1P LOW TLS S1 PS

LOBIS1PLT

#

#. ## ## # LOBI S1P# ESD, ## ## #, ##
#. ## ## # ## # ## #, TLS ####
####.

## #	##
## #	##
###	SJ ### # ##
##	## ##
###	####
Top	##
####	S1 PS / SR, ESD, FO, HRO
## #	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## #	0.525 kg
###	ASTM F2413:2018 EN ISO 20345:2022



BLK



ORA




GRN



TLS(#### # ##)

Safety Jogger # #### TLS ##
#. ##

####. ## ## TLS #### ##
#. ##
#.



##


#, ## # ## #, ##
#, ## # # ## #

#.



##

#.



##

#####. ## # ## # ## #
#.



##(SR)

SRA+SRB=SRC ##
#####. SR# ## # ## # ## #
#.



##

#####.

SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
####, ##, ##, ##

##:
##, ### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	##			
	##: ### ##	mg/cm²/h	1.2	≥ 0.8
	##: ### ##	mg/cm²	21	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	34.59	≥ 2
	##: ### ##	mg/cm²	277	≥ 20
###	SJ ### # ###			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	###/##			
	### ####(## ##)	mm³	119.4mm³(Density:1.3)	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.48	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.48	≥ 0.36
	SR ## ## - ## + #### - #### ## ##	##	0.36	≥ 0.19
	SR ## ## - ## + #### - ## ## ##	##	0.36	≥ 0.22
	### ## #	###	215	0.1 - 1000
	ESD #	###	75	0.1 - 100
	#### ## ##	J	25	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	NA	N/A
	#### ## # (## # ## ## 10kN)	mm	NA	N/A
	#### ## # (## # ## ## 200J)	mm	16	≥ 14
	#### ## # (## # ## ## 15kN)	mm	17	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.