

LOBIS1PLT

#####

```
#### ## ##### #####. ## ## LOBI S1P# ESD, ## # #, ##
## ## ##### ##### ## #####. ### ## ## ## ##, TLS #####
#####.
```

## ##	##
## ##	##
###	SJ ### # ###
##	## ## ##
###	###/##
Top	##
#####	S1 PS / SR, ESD, FO, HRO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.525 kg
###	ASTM F2413:2018 EN ISO 20345:2022



ORA



BLK



GRN




TLS(#### ## ###)

```

Safety Jogger # #### TLS ###
#### ##### # # # #####. ##
#### ##### # ###, ## #####
#####. ### ##### TLS #### ##
#### ## # ## #####. ##
#### ## ## #####.

```




##

```
## ## ## ## ##, ## # ##, ##
##### ## ##, ##, ## # ## ##
## ## ## # ## ## ## ## ##
## #####.
```



###

#####.



##

```
### ## ##### ##### ## #####
#####. ## ## ##### ## ## #
##### ## ##### ## #####.
```



##(SR)

```
### ##(SR),
### ##### SRA+SRB=SRC ###
#####. SR# ### ##### ### ##
## ## ##### ##### #####.
```



##

#####.

##:
####, ###, ##, ##

##:
##, ### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	##			
	##: ### ##	mg/cm²/h	1.2	≥ 0.8
	##: ### ##	mg/cm²	21	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	34.59	≥ 2
	##: ### ##	mg/cm²	277	≥ 20
###	SJ ### # ###			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	###/##			
	### ####(## ##)	mm³	119.4mm³(Density:1.3)	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.48	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.48	≥ 0.36
	SR ## ## - ## + #### - ##### ## ##	##	0.36	≥ 0.19
	SR ## ## - ## + #### - ## ## ##	##	0.36	≥ 0.22
	### ## #	###	215	0.1 - 1000
	ESD #	###	75	0.1 - 100
	#### ## ##	J	25	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	NA	N/A
	#### ## # (## # ## ## 10kN)	mm	NA	N/A
	#### ## # (## # ## ## 200J)	mm	16	≥ 14
	#### ## # (## # ## ## 15kN)	mm	17	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.