






MAGOS3MID

Safety JoggerMAGO S3 ### ## # ## # ##
#####. ## ##### ## ## ## #####. ##, ## # ##
#####.

## ##	#### ## ##
## ##	##
###	SJ # ##
##	## ## ##
###	##
Top	##
####	S3 / SRC, HRO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.720 kg
###	ASTM F2413:2018 EN ISO 20345:2011



##:
##, ##, ##, ## # ##, ###

##:
##, ## ##, ### ## ##, ## ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#### ## ##			
	##: ### ##	mg/cm²/h	4.47	≥ 0.8
	##: ### ##	mg/cm²	38	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	56.3	≥ 2
	##: ### ##	mg/cm²	451	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	##			
	### #####(## ##)	mm³	123	≤ 150
	### ## ## SRA: ###	##	0.30	≥ 0.28
	## SRA# ### ##: ##	##	0.34	≥ 0.32
	### ## ## SRB: ###	##	0.20	≥ 0.13
	## SRB# ### ##: ##	##	0.26	≥ 0.18
	### ## #	###	Dry:16.9, Wet:5.6	0.1 - 1000
	ESD #	###	Not applicable	0.1 - 100
	#### ## ##	J	30	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	Not applicable	N/A
	#### ## # (## # ## ## 10kN)	mm	Not applicable	N/A
	#### ## # (## # ## ## 200J)	mm	20.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	24.0	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.

