



# SAFETY JOGGER

PROFESSIONAL



#

## MAUD OB

### ## ### ## ### ##

MAUD ### ## ### ## ### ## ### ##. SR ### ##, ### ##, 3D  
##, ### ##, ### ## ### ## ### ## ### ## # ### ## ##.

|       |                                                                    |
|-------|--------------------------------------------------------------------|
| ## ## | ##                                                                 |
| ## ## | ##                                                                 |
| ###   | SJ # ##                                                            |
| ###   | ###/##                                                             |
| ####  | OB / SRA, E                                                        |
| ## ## | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5<br>JPN 21.5-26.5 / KOR 230-270 |
| ## ## | 0.280 kg                                                           |
| ###   | ASTM F2892:2024<br>EN ISO 20347:2012                               |



NAV



FUX



BLK



LGR



WHT



### 3D ##

##### ## ## ## ## ## # ##  
#####.




### ### ##

##### ## ## ## ## ## ## ##  
#####.



### ### #

### ## # ## ## ## ## ## ## ##  
### # ##.



### #### / SJ ##

##### © ### ## ## ## ## ##  
### ## ## ## ## ## ## ## ## ##  
SRC(SRA+ SRB) ### ##.



### SRA

### ## ## ## ## # ## ## ## ##  
## # ##. SRA ### ## ##  
### ## ## ## ## ## ## ## ## ##  
####.

SAFETY  
JOGGER  
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com

## ##:  
####, ##, ## # ##, ##

## ##:  
### ##

## ## ##:  
### ### ##### ##### ### ##### ## ##### ## #####. ### ##### ## ##### ## ##.

|       | ##                     | ## ##    | ##          | EN ISO 20347 |
|-------|------------------------|----------|-------------|--------------|
| ## ## | ##                     |          |             |              |
|       | ##: ### ##             | mg/cm²/h | 1.4         | ≥ 0.8        |
|       | ##: ### ##             | mg/cm²   | 15.5        | ≥ 15         |
| ## ## | ##                     |          |             |              |
|       | ##: ### ##             | mg/cm²/h | 28.9        | ≥ 2          |
|       | ##: ### ##             | mg/cm²   | 231.3       | ≥ 20         |
| ###   | SJ # ##                |          |             |              |
|       | ###: #####(##/##)(###) | ##       | 25600/12800 | 25600/12800  |
| ###   | ###/##                 |          |             |              |
|       | ### #####(## ##)       | mm³      | 81.0        | ≤ 150        |
|       | ### ## ## SRA: ###     | ##       | 0.48        | ≥ 0.28       |
|       | ## SRA# ### ##: ##     | ##       | 0.45        | ≥ 0.32       |
|       | ### ## ## SRB: ###     | ##       | N/A         | ≥ 0.13       |
|       | ## SRB# ### ##: ##     | ##       | N/A         | ≥ 0.18       |
|       | ### ## #               | ###      | N/A         | 0.1 - 1000   |
|       | ESD #                  | ###      | N/A         | 0.1 - 100    |
|       | #### ## ##             | J        | 34          | ≥ 20         |

### ##:  
##### ### ##### ##, ## ## ##### ## # #####. ## ##### ### Safety Jogger # ##### ##, ### ## ## #### ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com