

MODULO DELTA 06 LOW

Waterproof Low Occupational Shoes

A side profile view of a black safety shoe, likely a sneaker-style boot, featuring a thick, textured sole and a small logo on the side.


Upper	Abrasion Resistant Synthetic, Milled Full-Grain Leather
Lining	Membrane, Recycled Mesh
Footbed	SJ foam footbed
Outsole	BASF PU/Rubber (NBR)
Category	O6 / SR, SC, LG, ESD (≤ 100 MQ), FO, HRO
Size range	EU 37-48 / UK 4.0-13.0 / US 4.5-13.5 JPN 23-31.5 / KOR 240-315
Sample weight	0.555 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024



Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



The outsole resists high temperatures up to 300°C.



Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Waterproof footwear prevents liquids to enter into the shoe.



ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Heel energy absorption reduces the impact of jumps or running on the body of the wearer.

Industries:
Tactical, Uniform

Environments:
Extreme slippery surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Abrasion Resistant Synthetic, Milled Full-Grain Leather			
	Upper: permeability to water vapor	mg/cm ² /h	2.71	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	26	≥ 15
Lining	Membrane, Recycled Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	6.36	≥ 2
	Lining: water vapor coefficient	mg/cm ²	51	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	BASF PU/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm ³	117	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.44	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.42	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.29	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.32	≥ 0.22
	Antistatic value	MegaOhm	28.4	0.1 - 1000
	ESD value	MegaOhm	33	0.1 - 100
	Heel energy absorption	J	35	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



HEAD-TO-TOE
PROTECTION



Proudly ranked in the
top 1% by EcoVadis
for sustainability.



www.safetyjogger.com