



#

MILOS S1P MID S1 PS

MILOSS1PM

#####

S1P #####
ESD# #####. MILOS
S1P# #####.


##	##
##	##
###	SJ ###
##	###
###	###
Top	##
####	S1 PS / SR, ESD, FO, HRO
##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
##	0.550 kg
###	ASTM F2413:2018 EN ISO 20345:2022



RED



BLK




#####.




ESD# #####


#####. # 100#####
100### #####.



#####.



100% #####
#####.



#####.

##:
####, ##, ##, ##

##:
##, ### ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	##, ##			
	##: ### ##	mg/cm²/h	1.2	≥ 0.8
	##: ### ##	mg/cm²	21	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	34.59	≥ 2
	##: ### ##	mg/cm²	277	≥ 20
###	SJ ### # ###			
	###: #####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	###/##			
	### #####(## ##)	mm³	Relative volume loss: 140mm³ (Density:1.21)	≤ 150
	## ## # - ## + NaLS - ## ## ##	##	0.48	≥ 0.31
	## ## # - ## + NaLS - ## ## ##	##	0.48	≥ 0.36
	SR ## # - ## + ##### - ##### ##	##	0.36	≥ 0.19
	SR ## # - ## + ##### - ## ##	##	0.36	≥ 0.22
	### ## #	###	670	0.1 - 1000
	ESD #	###	19.1	0.1 - 100
	#### ##	J	25	≥ 20
Top	##			
	#### ## #(# # ##### 100J)	mm	N/A	N/A
	#### ## #(# # ## ## 10kN)	mm	N/A	N/A
	#### ## #(# # ## ## 200J)	mm	16.0	≥ 14
	#### ## #(# # ## ## 15kN)	mm	21.5	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com