



SAFETY JOGGER INDUSTRIAL



#

MODULO S1PS LOW PERF

MODULOS1PL

##


##. MODULO# #### ## ## #### ## ####. #
##, #### ##, #### ##, ESD, ## ##, ## ## ## ## ##
#####. ## ## #####.

## ##	#####
## ##	##
###	SJ # ##
##	## ## ##
###	### PU/### PU
Top	## ##
####	S1 PS / SR, SC, ESD, FO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.520 kg
###	ASTM F2413:2018 EN ISO 20345:2022 IS 15298 (Part 2): 2016



SJ FOAM

##, ## ## ## ##
#####. ## ## ##.



##

#####. SR ## ## ## ## ##
##.



##

##.



##

100% ## ## ## ##
#####.



##(SR)

SRA+SRB=SRC ##
#####. SR# ## ## ## ## ##
##.



##(SC)

##.



BLK



112



GRY

SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
####, ###, ##, ##

##:
##, ## #####

##:
#####. ### ##### ## ##### ### ##.

	##	## ##	##	EN ISO 20345
## ##	#####			
	##: ### ##	mg/cm²/h	8.20	≥ 0.8
	##: ### ##	mg/cm²	68	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	60.62	≥ 2
	##: ### ##	mg/cm²	485	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	### PU/### PU			
	### #####(## ##)	mm³	127mm³ (Density:1.09g/cm³)	≤ 150
	## ### ## - ### + NaLS - ## ### #####	##	0.33	≥ 0.31
	## ### ## - ### + NaLS - ## ## ###	##	0.42	≥ 0.36
	SR ### ## - ### + ##### - ##### ### ##	##	0.22	≥ 0.19
	SR ### ## - ### + ##### - ## ## ###	##	0.25	≥ 0.22
	### ## #	###	31.5	0.1 - 1000
	ESD #	###	21	0.1 - 100
	##### ## ##	J	31	≥ 20
Top	## ##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	15.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	21.0	≥ 14

##:

###, ## ## ##### ### # #####. ## ##### ### Safety Jogger # ##### ##, ### ## ## ### ## ##### ##### ### # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com