



## ##:  
####, ###, ##, ##  
  
## ##:  
### ##, ## ##### ##  
  
## ## ##:  
### ### ##### ##### ### ##### ### ##### ## #####. ### ##### ## ##### ### #####.

|       | ##                                     | ## ##    | ##                                | EN ISO 20345 |
|-------|----------------------------------------|----------|-----------------------------------|--------------|
| ## ## | #####                                  |          |                                   |              |
|       | ##: ### ###                            | mg/cm²/h | 8.20                              | ≥ 0.8        |
|       | ##: ### ##                             | mg/cm²   | 68                                | ≥ 15         |
| ## ## | ##                                     |          |                                   |              |
|       | ##: ### ###                            | mg/cm²/h | 60.62                             | ≥ 2          |
|       | ##: ### ##                             | mg/cm²   | 485                               | ≥ 20         |
| ###   | SJ # ##                                |          |                                   |              |
|       | ###: ####(##/##)(###)                  | ##       | Dry 25600 cycles/Wet 12800 cycles | 25600/12800  |
| ###   | ### PU/### PU                          |          |                                   |              |
|       | ### #####(## ##)                       | mm³      | 127mm³<br>(Density:1.09g/cm³)     | ≤ 150        |
|       | ## ### ## - ### + NaLS - ## ### #####  | ##       | 0.33                              | ≥ 0.31       |
|       | ## ### ## - ### + NaLS - ## ## ###     | ##       | 0.42                              | ≥ 0.36       |
|       | SR ### ## - ### + ##### - ##### ### ## | ##       | 0.22                              | ≥ 0.19       |
|       | SR ### ## - ### + ##### - ## ## ###    | ##       | 0.25                              | ≥ 0.22       |
|       | ### ## #                               | ###      | 31.5                              | 0.1 - 1000   |
|       | ESD #                                  | ###      | 21                                | 0.1 - 100    |
|       | ##### ## ##                            | J        | 31                                | ≥ 20         |
|       |                                        |          |                                   |              |
| Top   | ## ##                                  |          |                                   |              |
|       | #### ## # (## # ##### 100J)            | mm       | N/A                               | N/A          |
|       | #### ## # (## # ## ## 10kN)            | mm       | N/A                               | N/A          |
|       | #### ## # (## # ## ## 200J)            | mm       | 15.5                              | ≥ 14         |
|       | #### ## # (## # ## ## 15kN)            | mm       | 21.0                              | ≥ 14         |

### ##:  
##### ### ##### ##### ###, ## ## ##### ### # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ### ## ##### ##### ### # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com