

MODULO S3S LOW TLS



 ## ## ## ## ## ## ## ##
 #####. ## ## ## ## ##
 ##### ## ##### ## #####.



##:
####, ###, ####, ##, ##, ##

##:
##, ## #### ##, ## ##

##:
####.

	##	## ##	##	EN ISO 20345
## ##	#####			
	##: ### ##	mg/cm²/h	8.20	≥ 0.8
	##: ### ##	mg/cm²	68	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	60.62	≥ 2
	##: ### ##	mg/cm²	485	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	### PU/### PU			
	### ####(## ##)	mm³	127mm³ (Density:1.09g/cm³)	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.33	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.42	≥ 0.36
	SR ## ## - ## + #### - #### ## ##	##	0.22	≥ 0.19
	SR ## ## - ## + #### - ## ## ##	##	0.25	≥ 0.22
	### ## #	###	31.5	0.1 - 1000
	ESD #	###	21	0.1 - 100
	#### ## ##	J	31	≥ 20
Top	## ##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	15.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	21.0	≥ 14

##:
####, ## ## #### #### # ####. ## #### #### Safety Jogger # #### ##, ### ## ## ## ## #### #### #### # ####.



Solutions for every workplace
INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com