

MODULO S3S MID

#####

```
## #### ###. MODULO# ### ##### ## ## ##### ### #####. #
### ##### ##, ### ####, ### ###, ESD, ## ####, ## ## # ### ## ###
#####. ## ### #####.
```

## ##	#####
## ##	##
###	SJ # ##
##	## ## ##
###	### PU/### PU
Top	## ##
#####	S3S / SR, SC, ESD, CI, FO
## ##	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
## ##	0.580 kg
###	ASTM F2413:2018 EN ISO 20345:2022+A1:2024 IS 15298 (Part 2): 2016



##.



```
### #(SC)
### ## # # ## ### ### ###
#### #### ## ## ### ## ##
#### ## ### #####.
```




```
### ##(SR)
### ##### SRA+SRB=SRC ###
#####. SR# ### ##### ### ##
## ## ##### #####
```



#####



```
## ## ##
### ## ## ##### ## ## ##.
### ## ### 100% ## ## #####
####
```



```
## ##
### ## ##### ## #####
#####. ## ## ##### ## #
##### ## ##### ## #####.
```



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

##:
####, ###, ####, ##, ##, ##

##:
##, ## #### ##, ## ##

##:
####.

	##	## ##	##	EN ISO 20345
## ##	#####			
	##: ### ##	mg/cm²/h	8.20	≥ 0.8
	##: ### ##	mg/cm²	68	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	60.62	≥ 2
	##: ### ##	mg/cm²	485	≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	### PU/### PU			
	### ####(## ##)	mm³	127mm³ (Density:1.09g/cm³)	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.33	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.42	≥ 0.36
	SR ## ## - ## + #### - #### ## ##	##	0.22	≥ 0.19
	SR ## ## - ## + #### - ## ## ##	##	0.25	≥ 0.22
	### ## #	###	31.5	0.1 - 1000
	ESD #	###	21	0.1 - 100
	#### ## ##	J	31	≥ 20
Top	## ##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	15.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	21.0	≥ 14

##:
####, ## ## #### #### # ####. ## #### #### Safety Jogger # #### ##, ### ## ## ## ## #### #### #### # ####.



Solutions for every workplace
INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com